

# Hot Pressure Trailer Pressure-Pro Hot Pressure Washer

Portable and powerful cleaning power that goes wherever you need it. The Pressure Pro is built for heavy duty cleaning jobs with the right amount of heat and pressure that you need to get even the toughest jobs done. This industrial-strength trailer is DOT compliant and delivered turn-key and ready to use. A popular favorite, use the Pressure Pro for washing down equipment on the jobsite, water blasting, building exterior cleaning and environmental cleaning.



### **Features and Benefits**



#### **Features**

- Choice of gas or diesel powered engine
- 5.5 GPM at 3,500 PSI (or 4,000 PSI option)
- 3VX belt system for balanced power transfer
- Triplex plunger pump, industrial grade engine
- High pressure hose with quick connect trigger gun and 4 nozzles, and 180 degree swivel reel

#### **Benefits**

- DOT compliant for public roads
- · Starts easily and reliably with electric start
- Adjustable thermostat, to 120 degree rise
- Pressure relief valve for safety
- Ships turnkey, ready to use
- Manufacturer's warranty



## **Specifications**

Tank	EOO gollon "Algoo Posigeone" block poly tonk
	500 gallon "Algae Resistant" black poly tank
Engine	Honda GX630 24 HP (or Diesel Kohler
	KDW1003
	23.4 HP option), with electric start and battery
Pump	High Performance HP5535 Triplex plunger pumps
Power Transfer	3VX belt system for balanced power transfer
Volume	5.5 GPM
Pressure	3,500 PSI (4,000 PSI with diesel option)
	with safety pressure relief valve
Heating	Reliable diesel fired Beckett burners
	120 degree maximum rise
	Super-efficient insulated schedule 80 coil
	Stainless steel coil wrap, burner hood, control
	panel
	Adjustable thermostat
Fuel Tanks	I 5 gallon poly fuel tanks with fuel filters
Misc	2" Anti-Siphon Fill / Hose Bottom Fill
	Max-Flo 20% chemical injector
Hoses	50' high pressure hose with quick connects
	Spray gun/want assembly with quick connects
	4 color coded quick connect spray nozzles
Frame	6" steel frame with powder coated finish
	70" height $\times$ 80" wide $\times$ 210" length
Wheel Track	70"
Axels	Tandem leaf spring
Brakes	Surge Brakes
Tires	ST225/75D15
Hitch	2 5/16" ball; height adjustable
GVWR	6,000 lbs

