



Potable Water Trailer – 2035 Gallon NSF-61 Certified for Safe Water Containment

Large capacity water transport that you can count on. The 2035 gallon Potable Water Trailer's 12" I-Beam frame is built tough with many features including: a 16'x8' steel deck, tandem 12,000 lb Heavy Duty axels, electric brakes on both axels, two 12,000 lb rated drop leg jack stands, adjustable lunette eye coupler and DOT approved recessed lights. A rear mounted lockable hose storage box is also included.

The black polyethylene tank provides protection from algae growth and is NSF-61 certified for use with consumable water. It is outfitted with a 16" manhole and a hinged lockable lid. The elliptical tank design provides a lower center of gravity for safe towing and the molded-in baffles limit the amount of sway in the tank during transport. The standard pump for this trailer model is a Pacer certified NSF-61 2" food grade pump, coupled with a Honda Motor (145 gpm, 45 psi). The pump feeds a dual manifold system, one for each side of the trailer. Also included is a closed 2 1/2" Hydrant Fill Kit installed at the rear of the trailer with a dedicated check valve for filling the tank via fire hydrant.



2035 gallon Potable Water Trailer



Capacity	2035 gallons
Dimensions	Length: 21' 50", bed width 192", bed width 85 1/2"
Frame Size	Underclearance 14" at axle
Weight	Empty 5,450 lbs, loaded 21,750 lbs
GVWR	24,000 lbs
Axle	Tandem 12,000 lbs
Brakes	Electric on both axles
Wheels	Dual rims
Hitch (Coupler)	Adjustable lunette eye coupler ball
Tires	7:50 x 16" (10 ply rating)
Jackstand	Two, 12,000 lb drop leg style lbs
Tank	Tank Polyethylene 3/8" thick, elliptical, low profile design, repairable aif damaged, molded baffles, NSF-61 certified, algae resistant, 16" manhole, lockable lid.
Lights	DOT approved
Manufacturer's Warranty	3 years (tank), 1 year (trailer)
Pump/Engine	Honda engine, 145 gpm, 45 psi
Plumbing System	All steel manifold, five brass control valves to control functions, 2" steel pipe with dual rear spray heads, canal fill /drafting is a standard feature, 1 1/2" or 2" fire hose hookups, faucet for 5/8" hose, cox heavy duty hose reel, complete with 100' of 1" ID red rubber hose, 2 1/2" hydrant fill kit

Additional options include:

High pressure pump, hose and reel, double jacketed fire hose, NSF rated hoses, spare tires, military spigot array, remote controlled electric valve, locking tank lid, step ladder, tool boxes.

For more complete information on One Clarion products and solutions, visit us on the Web at www.clarionmunicipal.com.

Phone: (+1) 863-261-8388 | info@oneclarion.com

© 2022 One Clarion. All rights reserved. One Clarion terms and conditions apply.

All photos are representative only. Actual products may differ. Materials and specifications are subject to change without notice. Featured products in photos may include additional equipment or accessories.

