



# Water Trailers

## Water Transport Trailers

With 510-Gallon Water Tank & Semi-Trash Pump



MWT-0510-2MHD shown with  
hard suction option, TX-0008



The water trailer is equipped with a 510-gallon water tank, rear spray, hose hook-ups and more. It is an ideal choice for dust control, parking lot cleaning and water transportation.





# Water Trailers

## Water Transport Trailers

### TANK

- 510-gallon elliptical low profile 3/8-inch thick polyethylene
- 16-inch manhole with 4-inch vent and sump pump

### CENTRAL MANIFOLD

- Easy-to-operate butterfly brass valves

### PLUMBING

- 1½-inch fire hose hook-up with 50-foot x 1½-inch hose and fog nozzle
- Break-away hydrant fill with 25-foot x 2½-inch hose
- Dual rear spray heads
- Garden hose connector
- Manifold discharge system
- Water hammer prevention valve

### TRAILER

- DOT approved
- 12-inch under-clearance at axle
- 7,000-lb. side-mount crank jack
- Dual leaf spring suspension
- Rubber mounted sealed lights
- Wire storage basket
- Two safety chains with snap hooks
- (4) ST225-75 15-inch tires

### SEMI-TRASH PUMP

- 2-inch suction and discharge that handles solids up to 3/4-inch diameter
- Heavy-duty powder coated wraparound frame with 1-inch steel tubing
- Silicon carbide mechanical seals
- Precision molded cast iron impeller and volute for reduced vibration and wear

### LIMITED WARRANTIES

- 1 year trailer
- 2 year pump
- 3 year engine
- 3 year water tank

MODEL NUMBER	DISPLACEMENT/ENGINE	PUMP	HITCH	AXLES	BED FRAME	DIMENSIONS (LxWxH)	TRAILER WT. (EMPTY)	TRAILER WT. (LOADED)
MWT-0510-2MHD	196cc Honda GX200 OHV	2in. semi-trash	2in., ball	(2) 3,500 lb. tandem with hydraulic surge brakes	5ft.x8ft.	13.7x6.8x5.8ft.	1,580 lb.	5,900 lb.
MWT-0510-2MMD	212cc Mi-T-M OHV	2in. semi-trash	2in., ball	(2) 3,500 lb. tandem with hydraulic surge brakes	5ft.x8ft.	13.7x6.8x5.8ft.	1,580 lb.	5,900 lb.

### OPTIONS:

PART NUMBER	DESCRIPTION	FITS MODELS
TX-0008	Hard suction option – Allows you to draw water from an auxiliary source (pond, water pit, etc.). The fire hose is designed to be used with pressurized water and lays flat for easy storage.	All models
TX-0010	Adjustable trailer coupler hitch – Replaces the standard 2-inch ball hitch with a 2-inch trailer hitch with pin-style fastener trailer coupler and hinged ball socket	All models
TX-0019	Lunette ring hitch – Replaces the standard 2-inch ball hitch with a 3-inch integrated lunette ring for use with pintle hitches	All models
TX-0024	Water bypass – Allows you to bypass water from the outlet back to the tank. This can be used to reduce outlet pressure and flow for desired application	All models without the TX-0008 hard suction option

