




Ultra-Containment Berm[®] Comparison Guide



Description (Click for more information)	Cost	Drive-in/out	Set-up Required (beyond initial deployment)	Standard Height	Other Heights Available	Standard Material	Other Materials Available
<u>Collapsible Wall Model</u>	\$	-	Yes	12"	18", 24"	Copolymer-2000	PVC, XR5, Urethane
<u>Compact Model</u>	\$\$\$	-	Yes	12"	-	Copolymer-2000	PVC, XR5, Urethane
<u>Economy Model</u>	\$	-	Yes	12"	18", 24"	Copolymer-2000	PVC, XR5, Urethane
<u>Foam Wall Model</u>	\$\$	4 Sides	No	4"	2", 6"	Copolymer-2000	PVC, XR5, Urethane
<u>Modular Model (Gorilla Berm)</u>	\$\$\$	4 Sides	No	6"	-	PVC 38	Copolymer-2000, XR5, Urethane
<u>Rapid Rise</u>	\$\$	4 Sides	No	12"	18"	Copolymer-2000	PVC, XR5, Urethane
<u>Stake Wall Model</u>	\$\$\$	4 Sides	No	12"	-	Copolymer-2000	PVC, XR5, Urethane
<u>Ultimate Model</u>	\$\$	2 Sides	Only 2 Long Slides	12"	-	Copolymer-2000	PVC, XR5, Urethane
<u>Containment Wall</u>	\$\$\$	-	Yes	36"	12", 24"	Polyethylene	Call
<u>Mini Foam Wall Model</u>	\$	4 Sides	No	6"	-	PVC	Call

Berm Fabric Material	Weight	Thickness	Min Temp	Max Temp	Cold Crack	Tear Strength	Puncture Resistance
Copolymer-2000	30 oz/yd ²	30 mils nominal	-25°F	160°F	-25°F	30 lb _f , nominal	50 lb _f , typical
Urethane	23 oz/yd ²	25 mils nominal	-45°F	160°F	-45°F	58 lb _f , nominal	750 lb _f
PVC	22 oz/yd ²	24 mils nominal	-30°F	145°F	-30°F	46 lb _f , nominal	91 lb _f
XR5	30 oz/yd ²	30 mils minimum	-30°F	160°F	-30°F	55 lb _f , nominal	250 lb _f , minimum
PVC 38	24 oz/yd ²	38 mil	-30°F	145°F	-30°F	224 lb Warp/133 lb Fill	70 lb minimum



Collapsible Wall



Compact




Economy



Foam Wall



Modular (Gorilla)



Rapid Rise



Stake Wall



Containment Wall



Mini Foam Wall