



# PIPE SOCKS

## DEWATERING & FILTRATION

Also known as pipe socks, dewatering socks allow large volumes of water to filter through while successfully containing hydrocarbons such as oils and other contaminants.

Designed to attach easily to pipes or hoses, dewatering socks prevent pollutants from being discharged from the jobsite and help keep your project in compliance with NPDES and other regulations.

*The information and photos listed here are a guideline of the most common specifications for this product. As a service to you, we will provide comparable products fitting the specifications needed for your project and present you with the best priced options available.*



# PIPE SOCKS FOR DEWATERING & FILTRATION

Filter the flow

## Features:

- High performance geotextile fabric
- Fits multiple pipe/hose diameters
- Custom sizes available

## Benefits:

- Filters out silt, sediment, oils, grease and other hydrocarbons.
- Straps attached for easy installation.
- Supports compliance with stormwater regulations\*



*\*Helps comply with NPDES and 40 CFR 122.26 (1999) when used as a best management practice in Stormwater Pollution Prevention Plans (SWPPPs).*

## Oil & Sediment Pipe Sock Sizes:

- |                             |                         |                      |
|-----------------------------|-------------------------|----------------------|
| • 8" Diameter x 60" Length  | 1.7 gallon Oil Capacity | Ultra Part #9705-O/S |
| • 12" Diameter x 60" Length | 2.6 gallon Oil Capacity | Ultra Part #9706-O/S |
| • 16" Diameter x 60" Length | 3.5 gallon Oil Capacity | Ultra Part #9707-O/S |
| • Ask us about custom sizes |                         |                      |

# PIPE SOCKS FOR DEWATERING & FILTRATION

Filter the flow

## Specifications:

Mass Per Unit Area	11.0 oz/yd	ASTM 5261
Grab Tensile MD	118 lbs	ASTM D-4632
Grab Tensile TD	89 lbs	ASTM D-4632
Elongation at Peak MD	131%	ASTM D-4632
Elongation at Peak TD	172%	ASTM D-4632
Wide Width Tensile MD	33 lbs/in	ASTM D-4595
Wide Width Tensile TD	23 lbs/in	ASTM D-4595
Elongation at Break MD	110%	ASTM D-4595
Elongation at Break TD	156%	ASTM D-4595
Mullen Burst	214 lbs/in <sup>2</sup>	ASTM D-4786
Puncture Resistance	72 lbs	ASTM D-4833
Trapezoid Tear Strength MD	64 lbs	ASTM D-4533
Trapezoid Tear Strength TD	45 lbs	ASTM D-4533
Permittivity (Constant Head)	2.02 sec-l	ASTM D-4491
Permeability	0.72 cm/sec	ASTM D-4491
Flow Rate	151 gal/ft <sup>3</sup> /min	ASTM D-4491
Apparent Opening Size	100 microns	ASTM D-4751
Hydrocarbon Capacity	1.5 gal/yd <sup>2</sup>	

Note: We also offer a 60" pipe sock that fits pipes of 3" diameter, with a draw string for convenient fastening to pipes. This pipe sock will filter out sediment, oils, and other liquid hydrocarbons.

See also: [Pipe Sock Installation Guide](#)

For more complete information on One Clarion products and solutions, visit us on the web at [www.clarionmunicipal.com](http://www.clarionmunicipal.com).

Phone: [\(+1\) 863-261-8388](tel:+18632618388) | [info@oneclarion.com](mailto:info@oneclarion.com)

© 2022 One Clarion. All rights reserved. One Clarion terms and conditions apply.

All photos are representative only. Actual products may differ. Materials and specifications are subject to change without notice. Featured products in photos may include additional equipment or accessories.