

Track Pan Installation Instructions

IF THIS SYSTEM WILL HAVE “DRIVE ON/OVER” TRAFFIC

The Track Pans can only be driven on/over if they are installed on a bedding of adequate strength for the drive-over traffic and the bedding fully supports the underside of the pans.

The Track Pans can only be driven on if installed as above and **only if the vehicle has rubber tires.** Any form of hard wheel will damage the grating.

The Track Pans can only be driven on if installed as above and the drive over is in a relatively straight line. The anti-slip that is molded into the upper surface of the grating is very aggressive and **will be damaged by sharp turning of tires while a vehicle is on the grating.**

The Track Pans can only be driven on if installed as above and any starts or stops of a vehicle while on the grating is done slowly. The anti-slip that is molded into the upper surface of the grating is very aggressive and will be damaged by rapid starting or stopping while a vehicle is on the grating.

The Track Pans can only be driven on if installed as above and a “ramp” of adequate capacity (asphalt, concrete or other) is provided to raise the vehicle tires to the level of the upper surface of the grating. This “ramp-up” is required to avoid damage to the sides of the pans and grates.

Appendix A

Track Pan Replacement Parts and Accessories

Description	Qty.	Part #
1. Gasket “A”	1 ea.	9569
1. Gasket “B”	1 ea.	9568
1. Gasket “C”	1 ea.	9563
1. 3/4” NPT Bulkhead Fitting Ass’y (includes nut, donut-shaped gasket and rigid washer)	1 ea.	1073
1. Threaded Plug for Bulkhead Fitting	1 ea.	9960
1. Center Track Pan Grate (right), with cutout	1 ea.	9572
1. Center Track Pan Grate (left), with cutout	1 ea.	9571
1. Side Track Pan Grate, also Center Track Pan Grate without cutout	1 ea.	9573
1. 24” Rebar with Protective Cap	20-pack	9584
1. Wrench for Bulkhead Fittings	1 ea.	0464
1. 3 1/4” diameter gasket to seal off large “flow throughs” in Center and Side Track Pans	1 ea.	9557
1. 3” NPT Bulkhead Fitting Ass’y (includes nut, donut-shaped gasket and rigid washer)	1 ea.	9559

